



Glystantin[®]: The 3-fold premium protection for the cooling system

With 3-fold protection against corrosion, overheating and frost, Glystantin[®] protects the long-term functional reliability of cooling systems. Glystantin[®] – the original – is ideally suited for all engines and vehicle types.



www.glystantin.com

“Learn the most important basic rules on cooler protection from me.”

- Water alone is not enough to cool the system – only when it is mixed with protective Glystantin[®] concentrate can damage be avoided. The problem? Water without coolant concentrate expands when it freezes, boils at 100 degrees Celsius and causes rust to form more quickly.
- Never use undiluted coolant! With this mixture, you'll always be in safe hands: Glystantin[®]/Water: 50/50 (1/1 parts)
- Never mix coolants containing different technologies or coolants made by different manufacturers!
- You can find further information and tips about the right Glystantin[®] product for your vehicle, on our 32 language bottle label, on our orientation list or in the internet at www.glystantin.com



Always remember the following:

- Always completely change the coolant during repairs (flush and clean cooling system beforehand).
- With older cars, change coolant every 3 to 4 years.
- Use clean (not too hard) tap water, fully deionized or distilled water.
- Read your vehicle manufacturer's instructions.

➔ Note: Using coolant in the wrong way can leave your cooling system unprotected and may damage it!

Please find the right Glystantin[®] product on the rear page.



**Trucks
Engines
Construction
Machinery
Farm Machinery**

**"Find the right
Glysantin® product for
your vehicle here."**



**Glysantin®: The 3-fold premium
protection for the cooling system**
Comprehensive protection against
corrosion, overheating and frost



www.glysantin.com

Make	Country	Glysantin®	Specific series-type approval
Trucks:			
Avia Trucks	UK	G05®	
Cummins	US	G40® ●	G05® ●
Daewoo	KR	G30®	
DAF	NL	G30® ●	
Freightliner	US	G05®	G48®
GMC	US	G05®	
Iveco	D	G05®	G48®
Kenworth	US	G05®	
LIAZ	CZ	G05®	G48®
Mack	US	G05®	
MAN	D	G48® (before 11/2011) ●	
		G40® (after 12/2011) ●	
Mercedes-Benz	D	G48® (before 9/2011) ●	G05® (before 9/2011) ●
		G40® (after 10/2011) ●	
Mitsubishi Fuso	JP	G30®	
Nissan	JP	G30®	
Pegaso	E	G05®	G48®
Peterbilt	US	G05®	
Renault	F	G30®	
Sisu	FIN	G48®	G05®
Tatra	CZ	G05®	
Ural	RUS	G05®	
Volvo	S	G48® (before 2005) ●	G30® (after 2006)
Engines:			
Cummins	US	G40® ●	G05® ●
DAF	NL	G30® ●	
Deutz	D	G48® ●	G05®
MAN	D	G48® (before 11/2011) ●	
		G40® (after 12/2011) ●	
Mercedes-Benz	D	G48® (before 9/2011) ●	G05® (before 9/2011) ●
		G40® (after 10/2011) ●	
MTU	D	G48® ●	G05® ● G30® ●
Perkins	UK	G05®	G48®
Construction Machinery:			
ATLAS	D	G48®	
Demag	D	G05®	
GINAF	NL	G30®	G48®
Gottwald	D	G05®	G48®
Grove	US, D, IT	G05®	
Hiab	AT	G05®	
Liebherr	CH, D	G48® ●	G05®
Farm Machinery:			
CNH	NL	G05® (before 12/2013) ●	
		G30® (after 1/2014)	
Fendt	D	G48®	G05®
John Deere	US	G05® (before 2010) ●	
Jonsered	AT	G05®	
● = officially OEM approved			

The descriptions, designs, data and information contained herein are presented in good faith, and are based on BASF's current knowledge and experience. They are provided for guidance only, and do not constitute the agreed contractual quality of the product or a part of BASF's terms and conditions of sale. Because many factors may affect processing or application of the product, BASF recommends that the user carry out its own investigations and tests to determine the suitability of a product for its particular purpose prior to use. It is the responsibility of the recipient to ensure that any proprietary rights and existing laws and legislation are observed. No warranties of any kind, either expressed or implied, including, but not limited to, warranties of merchantability or fitness for a particular purpose, are made regarding products described or designs, data or information may be used without infringing the intellectual property rights of others. Any descriptions, designs, data and information given in this publication may change without prior information. The descriptions, designs, data and information furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for the descriptions, designs, data or information given or results obtained, all such being given and accepted at the reader's risk. (02/2013)

EVO 1514e
Status: 06/15

BASF SE
Carl-Bosch-Str. 38
67063 Ludwigshafen